

Screened control cable FABER[®] 210 F-CP



DERZEIT KEIN BILD VERFÜGBAR. | NO IMAGE AVAILABLE.

Application: This cable is specially installed in rubbish, sewage-treatment plants, composting works, animal stalls and green-houses. Suitable for installation for flexible use for medium mechanical, stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms as well as outdoors.

Construction and technical data:

Conductor material:	copper, bare
Conductor construction:	Class 5 = flexible
Insulation:	polypropylene
Core wrapping:	plastic foil
Screen:	copper braid
Sheathing material:	TPE
Colour of outer sheath:	black
Flame-retardant:	VDE 0482-332-1-2/IEC 60332-1-2
Halogen-free:	DIN EN 50267/IEC 60754
UV-resistant:	yes
Oil-resistant:	yes
Ozone-resistant:	yes
For outdoor use:	yes
Permitted outer cable temperature, fixed, °C:	-50 - +80 °C
Permitted outer cable temperature, moved, °C:	-40 - +80 °C
Bending radius, fixed installation:	6 x Ø
Bending radius, moving application:	20 x Ø
Insulation resistance:	20 MOhm _x km



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

FABER[®] 210 F-CP

Nominal voltage U_o: 300 V

Nominal voltage U: 500 V

part no.	part name	Ø [mm]	Cu	G [kg]
036035	OZ 2X0.5	5.9	36	42

Ø | outer diameter approx.

Cu | Copper weight (GER)

G | net weight per 1000