

Heat resistant pendant cord with steel cord H05V2V2D3-F (NYPLYw)



DERZEIT KEIN BILD VERFÜGBAR. | NO IMAGE AVAILABLE.

Application: As drawbars as well as for fixed installation in lights (not permitted for the connection of localvariable loads).
Breaking load of the strength member 250 N.

Construction and technical data:

Standard:	DIN EN 50525-2-11 (VDE 0285-525-2-11)
Conductor material:	copper, bare
Conductor construction:	Class 5 = flexible
Insulation:	PVC TI3
Self-supporting element:	Steel
Sheathing material:	PVC YM3
Flame-retardant:	VDE 0482-332-1-2/IEC 60332-1-2
Max. temperature at conductor, °C:	90 °C
Permitted outer cable temperature, fixed, °C:	5 - 90 °C



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

H05V2V2D3-F (NYPLYw)

Nominal voltage U_o:	300 V
Nominal voltage U:	500 V
Test voltage:	2 kV
Core identification:	green-yellow, blue, black, brown

part no.	part name	RI [Ohm/km]	I _{bl} [A]	Ø [mm]	Cu	G [kg]
032870	04G0.75 BK (NYPLYw-J) pendulum cord	26	12	9	29	72
032871	04G0.75 WH (NYPLYw-J) pendulum cord	26	12	9	29	72

RI | Conductor resistance

I_{bl} | Ampacity in air (30 °C)

Ø | outer diameter approx.

Cu | Copper weight (GER)

G | net weight per 1000