

# Compensation cable

## AGL Type RCB/SCB LI2G2G



DERZEIT KEIN BILD VERFÜGBAR. | NO IMAGE AVAILABLE.

**Application:** For connecting thermo elements to measuring electronics.

### Construction and technical data:

<b>Specification/Standard:</b>	DIN IEC 584
<b>Conductor material:</b>	PtRh10/Pt
<b>Conductor construction:</b>	fine stranded
<b>Insulation:</b>	silicone rubber
<b>Stranding unit:</b>	pair
<b>Sheathing material:</b>	silicone rubber
<b>Colour of outer sheath:</b>	orange
<b>Insulation/sheath colour:</b>	og(+)/wh(-)/og
<b>Flame-retardant:</b>	VDE 0482-332-1-2/IEC 60332-1-2
<b>Operating temperature:</b>	0 - +200 °C
<b>Permitted outer cable temperature, fixed, °C:</b>	-60 - +180 °C
<b>Permitted outer cable temperature, moved, °C:</b>	-5 - +180 °C
<b>Class:</b>	2 (+/- 2,5 °C)

*The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.*

### AGL Type RCB/SCB LI2G2G

**Test voltage:** 0.5 kV

part no.	part name	Ø [mm]	G [kg]
070622	Compensation cable Li2G2G 02X1.5 PtRh10/Pt WH/OG colour code acc. to IEC, type RCB/SCB	7.1	76

Ø | outer diameter approx.

G | net weight per 1000