

Communication cable with circuit integrity

JE-H(St)H FE180/E30 Fire signalisation cable



DERZEIT KEIN BILD VERFÜGBAR. | NO IMAGE AVAILABLE.

Application: For signal transmission between electronic devices, in computer systems of process control units in fire hazard rooms with a high concentration of people or material assets and for installation of circuits with circuit integrity E30/E90 according to DIN 4102 part 12, with tested cable systems. For fixed installation in dry and damp areas on certified carrier systems. By the special sheath printing -Brandmeldekabel- this cable is particularly designed for the use in fire signalisation systems.

Construction and technical data:

Conductor material:	copper, bare
Conductor construction:	Class 1 = solid
Insulation:	FRNC-compound HI1
Screen:	Foil
Drain wire:	yes
Sheathing material:	FRNC-compound HM2
Colour of outer sheath:	red
Flame-retardant:	VDE 0482-266-2-4/IEC 60332-3-24 (Cat. C)
Smoke density:	DIN EN 61034/IEC 61034
Halogen-free:	DIN EN 50267/IEC 60754
Fire-resistant:	FE 180
Circuit integrity:	E30
Permitted outer cable temperature, fixed, °C:	-30 - +70 °C
Bending radius, fixed installation:	7.5 x Ø



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

JE-H(St)H ... Bd FE180/E30 Fire signalisation cable

Maximum operating capacity:	120 nF/km
Core identification:	colours acc. to VDE 0815
peak operating voltage, V:	225 V

part no.	part name	DI [mm]	Ø [mm]	Cu [kg/km]	G [kg]
102101	01X2X0.8	0.8	7.1	15	61

part no.	part name	DI [mm]	Ø [mm]	Cu [kg/km]	G [kg]
100427	02X2X0.8	0.8	7.5	25	76
100428	04X2X0.8	0.8	9.3	45	130
100429	08X2X0.8	0.8	11.4	85	232
100430	12X2X0.8	0.8	13.5	126	318
100431	16X2X0.8	0.8	15	166	430
100432	20X2X0.8	0.8	16.5	206	514
100433	32X2X0.8	0.8	20.5	326	730
100434	40X2X0.8	0.8	22.1	407	962
100435	52X2X0.8	0.8	25.1	529	1200

DI	diameter conductor
Ø	outer diameter approx.
Cu	Copper weight (GER)
G	net weight per 1000