

# Fibre optic patch cable

## LC/APC to LSH/APC, G657.A1



**Application:** Singlemode fiber jumpers are used for telecom networks and also for high speed metropolitan and access networks. They are manufactured using LSZH cables, which conform to IEC, EIA, TIA and Telcordia standards. The OS2 fiber jumpers are terminated with standard connectors, providing optimum optical performance.

### Construction and technical data:

<b>Strength member:</b>	aramide
<b>Sheathing material:</b>	halogen-free
<b>Colour of outer sheath:</b>	yellow
<b>Flame-retardant:</b>	IEC 60332-1-2
<b>Permitted operating temperature:</b>	-20 - +75 °C
<b>Maximum tensile strength (installation), N:</b>	100 N
<b>Plug A (patch cable):</b>	LC/APC
<b>Plug B (patch cable):</b>	LSH/APC

*The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.*

Properties

	Optical Properties	value	Standard
Plugs 1 LC/APC (green)	Optical Properties	value	Standard
	IEC Random Mating	Grade B	IEC 61755-1
	Attenuation max. (IL)	≤ 0.2 dB	IEC 61300-3-4
	Attenuation/Master (IL)	0.1 dB	IEC 61300-3-4
	Attenuation/Random (IL)	≤ 0.2 dB	IEC 61300-3-34
	Return loss (RL)	≥ 60 dB	IEC 61300-3-6
Plugs 2 LSH/APC (green)	IEC Random Mating	Grade B	IEC 61755-1
	Attenuation max. (IL)	≤ 0.2 dB	IEC 61300-3-4
	Attenuation/Master (IL)	0.1 dB	IEC 61300-3-4
	Attenuation/Random (IL)	≤ 0.2 dB	IEC 61300-3-34
	Return loss (RL)	≥ 60 dB	IEC 61300-3-6
cable	Version	Simplex, 2 mm	Duplex, 2 mm, Figure-8
fibres	Fibre class	Bend Insensitive Fibre G657.A1	

Fibre optic patch cord LC/APC to LSH/APC, G657.A1

**Fibre attenuation @1310 nm cabled:** 0.36 dB/km

**Fibre attenuation @1550 nm cabled:** 0.25 dB/km

**Macro bending loss @1550 nm (10 turns Ø30 mm):** ≤ 0.3 dB

part no.	part name	Number of fibres [n]	l [m]	w [mm]	h [mm]	Ø [mm]	G [kg]
072020	Patch cord simplex LC/APC - LSH/APC E9/125 G657.A1 yellow -0.5m-	1	0.5			1.6	7.2
071991	Patch cord simplex LC/APC - LSH/APC E9/125 G657.A1 yellow -1.0m-	1	1			1.6	6
071992	Patch cord simplex LC/APC - LSH/APC E9/125 G657.A1 yellow -2.0m-	1	2			1.6	7
071994	Patch cord simplex LC/APC - LSH/APC E9/125 G657.A1 yellow -3.0m-	1	3			1.6	8
071995	Patch cord simplex LC/APC - LSH/APC E9/125 G657.A1 yellow -5.0m-	1	5			1.6	14
072336	Patch cord simplex LC/APC - LSH/APC E9/125 G657.A1 yellow -7.0m-	1	7			1.6	56.9
071997	Patch cord simplex LC/APC - LSH/APC E9/125 G657.A1 yellow -10.0m-	1	10			1.6	24
072308	Patch cord duplex LC/APC - LSH/APC E9/125 G657.A1 yellow -0.5m-	2	0.5	3.2	1.6		16
072309	Patch cord duplex LC/APC - LSH/APC E9/125 G657.A1 yellow -1.0m-	2	1	3.2	1.6		19.1
072310	Patch cord duplex LC/APC - LSH/APC E9/125 G657.A1 yellow -2.0m-	2	2	3.2	1.6		25.4
072311	Patch cord duplex LC/APC - LSH/APC E9/125 G657.A1 yellow -3.0m-	2	3	3.2	1.6		31.7
072312	Patch cord duplex LC/APC - LSH/APC E9/125 G657.A1 yellow -5.0m-	2	5	3.2	1.6		44.3
072313	Patch cord duplex LC/APC - LSH/APC E9/125 G657.A1 yellow -7.0m-	2	7	3.2	1.6		56.9
072314	Patch cord duplex LC/APC - LSH/APC E9/125 G657.A1 yellow -10.0m-	2	10	3.2	1.6		75.8

Number of fibres	Number of fibres
l	Length, m (cable with assemblies)
w	Width
h	Height
Ø	outer diameter approx.
G	net weight per 1000