

Reeling cable

Reelingflex AL



DERZEIT KEIN BILD VERFÜGBAR. | NO IMAGE AVAILABLE.

Application: Reeling cables are designed for power supply connections to all types of mobile equipment and vehicles used in quarrying, open-cast mining and other large scale civil engineering operations. For applications in mining and milling sites, construction plants, industry etc. The cable can also be used as a festoon cable.

Construction and technical data:

Conductor material:	aluminium
Conductor construction:	Class 5 = flexible
Insulation:	HEPR
Pilot conductor:	copper, bare, class 5, halogen free, EVI-1, red
Material inner sheath:	polyurethan
Self-supporting element:	Kevlar®
Sheathing material:	polyurethan
Colour of outer sheath:	yellow
Flame-retardant:	VDE 0482-332-1-2/IEC 60332-1-2
Halogen-free:	yes
UV-resistant:	yes
Oil-resistant:	EN 60811-2-1
Ozone-resistant:	yes
Max. temperature at conductor, °C:	90 °C
Max. short circuit temperature at conductor, °C:	250 °C
Permitted outer cable temperature, fixed, °C:	-40 - +80 °C
Permitted outer cable temperature, moved, °C:	-30 - +80 °C
Bending radius, fixed installation:	6 x Ø
Bending radius, moving application:	8 x Ø
Operating speed random, m/min.:	180 m/min.
Operating speed festoon, m/min.:	200 m/min.



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

Reelingflex AL

Nominal voltage U₀: 0.6 kV

Nominal voltage U: 1 kV

Test voltage: 3.5 kV

part no.	part name	RI [Ohm/km]	I _{bl} [A]	Ø [mm]	Al	Cu	G [kg]
038183	3X25 + 3G6 + 2X2.5	1.285	75	28	251	48	750
038184	3X35 + 3G6 + 2X2.5	0.915	94	30	332	48	1000
038185	3X50 + 3G10 + 2X2.5	0.645	114	34.2	486	48	1250
038186	3X70 + 3G16 + 2X2.5	0.445	146	39	697	48	1600
038187	3X95 + 3G16 + 2X2.5	0.34	177	43.1	903	48	2150
038188	3X120 + 3G25 + 2X2.5	0.266	205	47.3	1170	48	2650
038189	3X150 + 3G25 + 2X2.5	0.213	235	54.7	1490	48	3380
038190	3X185 + 3G35 + 2X2.5	0.174	267	59.3	1782	48	4000
038191	3X240 + 3G50 + 2X2.5	0.132	319	63.5	2340	48	4900

RI	Conductor resistance
I _{bl}	Ampacity in air (30 °C)
Ø	outer diameter approx.
Al	Aluminium weight (GER)
Cu	Copper weight (GER)
G	net weight per 1000