

# Coaxial cable RG 188 A/U



DERZEIT KEIN BILD VERFÜGBAR. | NO IMAGE AVAILABLE.

**Application:** For data- and signal transmission in RF-bands with low losses and interferences.

## Construction and technical data:

**CPR-performance:** on request

**Permitted outer cable temperature, fixed, °C:** -5 - +70 °C



*The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.*

## RG 188 A/U

<b>Colour of outer sheath:</b>	white
<b>inner conductor material:</b>	copper plated steel wire, stranded, silver plated
<b>Insulation:</b>	PTFE
<b>Insulation diameter:</b>	1.52 mm
<b>Outer screen:</b>	copper braiding, silver plated
<b>Sheathing material:</b>	PFA 51Y
<b>Minimum bending radius:</b>	25 x Ø
<b>Operating temperature:</b>	-55 - +200 °C
<b>Impedance, ohm:</b>	50 Ohm
<b>Capacity:</b>	96 nF/km
<b>Velocity factor:</b>	0.7 v/c
<b>Test voltage:</b>	1.7 kV

part no.	part name	Ø [mm]	Cu [kg/km]	G [kg]
101793	RG 188 A/U PFA	2.6	8,8	15

Ø	outer diameter approx.
Cu	Copper weight (GER)
G	net weight per 1000