

Screened single core cable YSLYCY-O POWER UL/CSA



DERZEIT KEIN BILD VERFÜGBAR. | NO IMAGE AVAILABLE.

Application: Screened control and power cable for industry and machinery environment with increased electromagnetic compatibility requirements for indoor applications. For installation in dry and damp rooms. The cable is oil-resistant.

Construction and technical data:

Conductor material:	copper, bare
Conductor construction:	Class 5 = flexible
Insulation:	PVC TI3 - UL 90 °C - UL 758
Screen:	tinned copper braid
Screen coverage:	85 %
Sheathing material:	PVC TM3 - UL 90 °C - UL 758
Flame-retardant:	VDE 0482-266-2-4/IEC 60332-3-24 (Cat. C)
Oil-resistant:	yes
Max. temperature at conductor, °C:	90 °C
Permitted outer cable temperature, fixed, °C:	-40 - +90 °C
Permitted outer cable temperature, moved, °C:	-5 - +90 °C
Bending radius, fixed installation:	4 x Ø
Bending radius, moving application:	13 x Ø



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

YSLYCY POWER UL/CSA

Nominal voltage U₀:	0.6 kV
Nominal voltage U:	1 kV
Test voltage:	10000 kV

part no.	part name	Ø [mm]	Cu	G [kg]
037951	YSLYCY-O POWER UL/CSA 01x70 2/0 0.6/1 kV BK	20.7	763	1065
037952	YSLYCY-O POWER UL/CSA 01x95 3/0 0.6/1 kV BK	21.7	1002	1290
037953	YSLYCY-O POWER UL/CSA 01x120 4/0 0.6/1 kV BK	23	1248	1534
037954	YSLYCY-O POWER UL/CSA 01x185 350 MCM 0.6/1 kV BK	28	1897	2310

Ø	outer diameter approx.
Cu	Copper weight (GER)
G	net weight per 1000